



Dock-to-Ground Ramp Specifications (No Wheels or Undercarriage)

Steel Ramp with Steel Grating

Capacity	Length	Overall Width	Usable Width	Approx. Weight	Height Range	Model Number
12,000	30'	96"	88"	6,400	37" – 60"	DGS12-96-30
16,000	20'	70"	62"	3,240	22" – 38"	DGS16-70-20
16,000	20'	84"	76"	3,750	22" – 38"	DGS16-84-20
16,000	20'	96"	88"	4,200	22" – 38"	DGS16-96-20
16,000	30'	70"	62"	5,020	37" – 60"	DGS16-70-30
16,000	30'	84"	76"	5,770	37" – 60"	DGS16-84-30
16,000	30'	96"	88"	6,475	37" – 60"	DGS16-96-30
20,000	30'	70"	62"	5,175	37" – 60"	DGS20-70-30
20,000	30'	84"	76"	5,925	37" – 60"	DGS20-84-30
20,000	30'	96"	88"	6,600	37" – 60"	DGS20-96-30
25,000	30'	70"	62"	5,280	37" – 60"	DGS25-70-30
25,000	30'	84"	76"	6,050	37" – 60"	DGS25-84-30
25,000	30'	96"	88"	6,720	37" – 60"	DGS25-96-30

Standard Features:

- 15" Lip
- 6" Curbs
- Safety Chains and Mounting Bracket

****Larger ramps available upon request****